

Battery powered plastic strapping tools for heavy strapping

**Characteristics**

Strapping qualities:		Polypropylene (PP) and Polyester (PET)
Strapping dimensions:	widths	19.0 – 25.0 mm / 3/4 – 1"
	thicknesses	0.40 – 1.53 mm / .016 - .060"
Weight:		5.7 kg / 12.6 lbs
Dimension:		L395 x W137 x H143 mm
Average seal strength:		up to 75% (dependent on strap quality)
Strap tension:		1200 – 6000 N / 270 – 1350 lbs (adjustable)
Tensioning speed:		70 – 87 mm/s / 2.8 – 3.4 inch/s
Power supply:	Battery	28VDC / 3.0 Ah Li-Ion
Suspension bracket (optional)		

Advantages

- Ergonomic design with small handle
- Well balanced tool for all strapping positions
- Simple one-handed operation
- Exceptional tension force
- Sealing time adjustable
- Easy strap threading; Both straps are inserted together
- Welding lever locks in bottom position and allows the preparation of the next strapping during welding and cooling
- Tools welds without tension (strap repair)
- Quick battery exchange
- Latest Li-Ion battery technology

Chart of types model P330

Item No.	Model	Strap widths		Strap thicknesses		Max. Tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/sec.	inch/sec.
43.0254	P330/19/0.80-1.19	19	3/4	0.80-1.19	.031-.047	6000	1350	70-87	2.8-3.4
43.0256	P330/19/1.20-1.53	19	3/4	1.20-1.53	.047-.060	6000	1350	70-87	2.8-3.4
43.0262	P330/25/0.40-0.79	25	1	0.40-0.79	.016-.031	6000	1350	70-87	2.8-3.4
43.0264	P330/25/0.80-1.19	25	1	0.80-1.19	.031-.047	6000	1350	70-87	2.8-3.4
43.0266	P330/25/1.20-1.35	25	1	1.20-1.35	.047-.053	6000	1350	70-87	2.8-3.4

Battery chargers for model P330

Item No.	Model	Charging type	Tension	Countries
N5.4435	Battery standard charger	Li-Ion	220-240 V / 50-60 Hz	A, B, BG, BIH, BOL, BR, CH, CL, CZ, D, DK, DZ, E, EAS, EST, ET, EY, F, FIN, GE, GR, H, HK, HR, I, IL, IND, IR, IRQ, IS, JOR, KSA, KWT, L, LAR, LT, LV, MA, MC, MK, MOC, N, NL, P, PK, PE, PL, PRC, PY, RA, RCH, RI, RL, RO, ROK, ROU, RP, RUS, S, SK, SLO, SYR, THA, TN, TR, UA, UAE, YU, YV, Z, ZA, ZW
N5.4437	Battery standard charger	Li-Ion	120 V / 50-60 Hz	BR, C, CDN, CO, CR, DOM, EC, GCA, J, JA, KSA, LB, MEX, NIC, PA, Puerto Rico, RC, RP, USA, YV
N5.4439	Battery standard charger	Li-Ion	220-240 V / 50-60 Hz	BRN, BRU, CY, EAK, EAT, GB, IRL, M, MAL, OM, SGP, Y
N5.4441	Battery standard charger	Li-Ion	220-240 V / 50-60 Hz	AUS, NZ

Replacement battery for model P330

Item No.	Model	Tension	Power
N5.4326	Accu Li-Ion	28VDC	3.0 Ah

Accessories

P32.0112	Standard suspension bracket
P33.0120	Suspension bracket for alternating positions
P33.0121	Wearing sheet for rough surfaces
P33.0122	Wearing plate for rough surfaces
P32.2061	Turning button kit